

# A view of 0 or 1 elements: `views::nullable` And a concept to constrain maybes

Steve Downey (sdowney@gmail.com)

Document #: P1255R13  
Date: 2024-05-22  
Project: Programming Language C++  
Audience: LEWG

## Abstract

This paper proposes a range adaptor `views::nullable` which adapts nullable types—such as `std::optional` or pointer to object types—into a range of the underlying type.

It also proposes a concept `maybe`, that types which are contextually convertible to `bool` and dereferenceable model.

## Contents

<b>1 Before / After Table</b>	<b>2</b>
<b>2 Motivation</b>	<b>3</b>
<b>3 Borrowed Range</b>	<b>4</b>
<b>4 Monadic Operations</b>	<b>4</b>
<b>5 Maybe Concept and Functions</b>	<b>5</b>
<b>6 Design</b>	<b>6</b>
<b>7 Freestanding</b>	<b>6</b>
<b>8 Implementation</b>	<b>6</b>
<b>9 Proposal</b>	<b>6</b>
<b>10 Wording</b>	<b>7</b>
<b>11 Impact on the standard</b>	<b>11</b>
<b>References</b>	<b>13</b>

## Changes Since Last Version

- **Changes since R12,**
  - Removal of `views::maybe` in favor of `range optional`
  - `std::maybe` concept
  - Free functions on `maybe` types such as `optional` and `pointers`.

- Changes since R12,
  - Paper system issues—No text changes over R11

## 1 Before / After Table

```

auto opt = possible_value();
if (opt) {
    // a few dozen lines ...
    use(*opt); // is *opt Safe ?
}

```

```

for (auto&& opt :
      views::nullable(possible_value())) {
    // a few dozen lines ...
    use(opt); // opt is Safe
}

```

```

std::optional o{7};
if (o) {
    *o = 9;
    std::cout << "o=" << *o << " prints 9\n";
}
std::cout << "o=" << *o << " prints 9\n";

```

```

std::optional o{7};
for (auto&& i
      : views::nullable_view<std::optional<int>&>(o)) {
    i = 9;
    std::cout << "i=" << i << " prints 9\n";
}
std::cout << "o=" << *o << " prints 9\n";

// if range for is too much magic
if (auto v = views::nullable_view<std::optional<int>&>(o);
     std::begin(v) != std::end(v)) {
    auto itr = std::begin(v);
    *itr = 10;
    std::cout << "*itr=" << *itr << " prints 10\n";
}
std::cout << "o=" << *o << " prints 10\n";

```

```

std::vector<int> v{2, 3, 4, 5, 6, 7, 8, 9, 1};
auto test = [](int i) -> std::optional<int> {
    switch (i) {
    case 1:
    case 3:
    case 7:
    case 9:
        return i;
    default:
        return {};
    }
};

auto&& r = v | ranges::views::transform(test) |
           ranges::views::filter(
               [](auto x) { return bool(x); }) |
           ranges::views::transform(
               [](auto x) { return *x; }) |
           ranges::views::transform([](int i) {
               std::cout << i;
               return i;
           });
for (auto&& i : r) {
};

```

```

std::vector<int> v{2, 3, 4, 5, 6, 7, 8, 9, 1};
auto test = [](int i) -> std::optional<int> {
    switch (i) {
    case 1:
    case 3:
    case 7:
    case 9:
        return i;
    default:
        return {};
    }
};

auto&& r =
v | ranges::views::transform(test) |
  ranges::views::transform(views::nullable) |
  ranges::views::join |
  ranges::views::transform([](int i) {
      std::cout << i;
      return i;
  });
for (auto&& i : r) {
};

```

```

std::vector<int> v{2, 3, 4, 5, 6, 7, 8, 9, 1};

auto test = [](int i) -> optional<int> {
    switch (i) {
    case 1:
    case 3:
    case 7:
    case 9:
        return optional{i};
    default:
        return optional<int>{};
    }
};

auto&& r = v | ranges::views::transform(test) |
           ranges::views::join |
           ranges::views::transform([](int i) {
               std::cout << i;
               return i;
           });
for (auto&& i : r) {
};

```

## 2 Motivation

In writing range transformation it is useful to be able to lift a value into a view that is either empty or contains the value. `std::optional` fills this function. For nullable types, types which model maybe, constructing an empty view for disengaged values and providing a view to the underlying value is useful as well.

```
int fortytwo = 42;
int sixbynine = 54;

std::vector<int*> v{&fortytwo, nullptr, &sixbynine};

auto r = std::views::join(std::views::transform(v, views::nullable));

for (auto i : r) {
    std::cout << i << '\t'; // prints 42 and 54 skipping the nullptr
}
std::cout << std::endl;
```

The maybe protocol that `views::nullable` adapts is inherently unsafe because it models unsafe pointer semantics. If a nullable type is disengaged, using the dereference operator `operator*()` is undefined behavior, in practice reading from a union with the wrong type engaged. The allowed operations of `views::nullable` are all, in themselves, safe, and using the adapter can lead to safer code.

An example is using `views::nullable` in range based for loops, allowing the contained nullable value to not be dereferenced within the body. This is of small value in small examples in contrast to testing the nullable in an if statement, but with longer bodies the dereference is often far away from the test. This can be a particular issue in doing code reviews where the test, if it exists, is not visible. Often the first line in the body of the `if` is naming the dereferenced nullable, and lifting the dereference into the for loop eliminates some boilerplate code, the same way that range based for loops do.

```
{
    auto opt = possible_value();
    if (opt) {
        // a few dozen lines ...
        use(*opt); // is *opt safe ?
    }
}

for (auto&& opt :
    views::nullable(possible_value())) {
    // a few dozen lines ...
    use(opt); // opt is safe
}
```

Of course, if the maybe is empty, there is nothing in the view to act on.

```
auto oe = std::optional<int>{};
for (int i : views::nullable(oe))
    std::cout << "i=" << i
                << '\n'; // does not print
```

Converting an optional type into a view can make APIs that return optional types, such as lookup operations, easier to work with in range pipelines.

```

std::unordered_set<int> set{1, 3, 7, 9};

auto flt = [=](int i) -> std::optional<int> {
    if (set.contains(i))
        return i;
    else
        return {};
};

for (auto i : ranges::iota_view{1, 10} |
      ranges::views::transform(flt)) {
    for (auto j : views::nullable(i)) {
        for (auto k : ranges::iota_view(0, j))
            std::cout << '\a';
        std::cout << '\n';
    }
}

```

### 3 Borrowed Range

A `borrowed_range` is one whose iterators cannot be invalidated by ending the lifetime of the range.

The reference specializations of `nullable_view` are borrowed. Iterators refer to the underlying object directly.

All instantiations of `nullable_view` over a pointer to object are borrowed ranges. The iterator refers to the address of the object pointed to without involving any addresss in the view.

A `nullable_view<shared_ptr>`, however, is not a borrowed range, as it participates in ownership of the `shared_ptr` and might invalidate the iterators if upon the end of its lifetime it is the last owner.

An example of code that is enabled by borrowed ranges, if unlikely code:

```

num = 42;
int k = *std::ranges::find(views::nullable(&num), num);

```

Providing the facility is not a significant cost, and conveys the semantics correctly, even if the simple examples are not hugely motivating. In particular there is no real implementation impact, other than providing template variable specializations for `enable_borrowed_range`.

### 4 Monadic Operations

It is not feasible to give `nullable_view` a direct monadic interface as it would require, for example, construction of a type that dereferences to `U` to support `transform` over `T -> U`, but that is not in general possible in the C++ type system. The additional level of indirection built in to `nullable_view` makes this infeasible.

#### 4.1 Reference Specialization

Having worked with the `reference_wrapper` support for some time, the ergonomics are somewhat lacking. In addition, many of the Big Dumb Business Objects that are the result of lookups, or filters, and are thus good candidates for optionality, are also not good at move operations, having dozens of individual members that are a mix of primitives, strings, and sub-BDOs, resulting in complex move constructors. In addition, many old and well tested functions will mutate these objects, rather than making copies, using a more object oriented than value oriented style.

For these reasons, supporting the common case of reference semantics ergonomically is important. Folding the implementation of `reference_wrapper` into a template specialization for `T&` provides good ergonomics. The type `nullable_view` does not support assignment from the underlying type, so the only question for semantics is assignment from another instance of the same type. The semantics of

`std::reference_wrapper` are well established and correct, where the implementation pointer is reassigned, putting the assignee into the same state as the assigned. These are the same semantics currently proposed for `optional<T&>`.

The range adaptor `views::nullable` only produces the non-reference specialization. As range code is strongly rooted in value semantics, providing reference semantics without ceremony seems potentially dangerous. Having it dependent on the value category of the expression would make it far too easy to produce reference types that would dangle. If the pattern becomes common, providing an instance of the function object with a distinct name would be non-breaking for anyone. Using the constructor form is not a particular burden.

This means that all of the operations on `nullable_view` are directly safe. To construct a non-safe operation is possible, but looks unsafe in code. For example:

```
nullable_view<int> o1{42};  
// ...  
assert(*(o1.data()) == 42));
```

Dereferencing the result of `data()` without a check for null is of course unsafe, but in a way that should be visible to programmers, reviewers, and tools.

## 5 Maybe Concept and Functions

The `nullable_view` adapts types that model maybe. In addition to the adapter, this paper proposes exposing the concept and the most generally used helper functions for maybes

- `value_or`—The referred to value or an alternative
- `reference_or`—A reference to the referred to value or a reference to an alternative
- `or_invoke`—The referred to value or a function to invoke to return a value
- `yield_if`—An optional holding a value or not conditioned on a boolean

These mirror functions commonly found in optional implementations, however most of the implementations were specified before traits like `common_reference` were standardised, and can not be fixed today. For example `std::optional<T>::value_or(U)` returns a T.

The concept is very minimal, as most uses of a maybe impose few constraints.

```
template <class T>  
concept maybe = requires(const T t) {  
    bool(t);  
    *(t);  
};
```

Figure 1: concept maybe

This ensures that a user type provides a conversion to `bool` and a dereference operator that can be used for `const` qualified types.

The implementation of each of the functions is relatively straightforward, albeit somewhat annoying.

```
template <class T, class R = optional<decay_t<T>>>  
constexpr auto yield_if(bool b, T&& t) -> R {  
    return b ? forward<T>(t) : R{};  
}
```

Figure 2: yield\_if

```

template <maybe T,
           class U,
           class R = common_reference_t<iter_reference_t<T>, U&&>>
constexpr auto reference_or(T&& m, U&& u) -> R {
    static_assert(!reference_constructs_from_temporary_v<R, U>);
    static_assert(!reference_constructs_from_temporary_v<R, T&>);
    return bool(m) ? static_cast<R>(*m) : static_cast<R>((U&&)u);
}

```

Figure 3: reference\_or

```

template <maybe T,
           class U,
           class R = common_type_t<iter_reference_t<T>, U&&>>
constexpr auto value_or(T&& m, U&& u) -> R {
    return bool(m) ? static_cast<R>(*m) : static_cast<R>(forward<U>(u))
}

```

Figure 4: value\_or

```

template <maybe T,
           class I,
           class R = common_type_t<iter_reference_t<T>,
                                 invoke_result_t<I>>>
constexpr auto or_invoke(T&& m, I&& invocable) -> R {
    return bool(m) ? static_cast<R>(*m) : static_cast<R>(invocable());
}

```

Figure 5: or\_invoke

## 6 Design

The type `nullable_view` has the semantics of zero or one objects based on if the underlying nullable object does or does not have a value, as indicated by the maybe being truthy or falsy.

## 7 Freestanding

The type `nullable_view` naturally meets the requirements for freestanding, as do the concept and proposed functions.

## 8 Implementation

A publicly available implementation at [https://github.com/steve-downey/view\\_maybe](https://github.com/steve-downey/view_maybe). There are no particular implementation difficulties or tricks. The declarations are essentially what is quoted in the Wording section and the implementations are described as effects.

## 9 Proposal

Add a range adaptor object

`views::nullable` a range adaptor over a `nullable_object` producing a view into the nullable object.

A maybe object is one that is both contextually convertible to `bool` and for which the type produced by dereferencing is an equality preserving object. Non void pointers, `std::optional`, and the proposed `std::expected` [P0323R9] types all model *maybe*. Function pointers do not, as functions are not objects. Iterators do not generally model *maybe*, as they are not required to be contextually convertible to `bool`.

The generic type `std::nullable_view`, which is produced by `views::nullable` is further specialized over reference types, such that operations on the iterators of the range modify the object the range is over, if and only if the object exists.

## 10 Wording

Modify 22 General utilities library[utilities]

### ◆.1 Maybe Types [maybe]

#### ◆.◆.1 In general [maybe.general]

- <sup>1</sup> Subclause ◆.1 describes the concept `maybe` that represents types that model optionality and functions that operate on such types.

#### ◆.◆.2 Header `<maybe>` synopsis [maybe.syn]

```
namespace std {
    // ??, class template maybe
    template <class T>
    concept maybe = requires(const T t) {
        bool(t);
        *(t);
    };

    template <maybe T, class U, class R>
    constexpr auto value_or(T&& m, U&& u) -> R;

    template <maybe T, class U, class R>
    constexpr auto reference_or(T&& m, U&& u) -> R;

    template <maybe T, class I, class R>
    constexpr auto or_invoke(T&& m, I&& invocable) -> R;
}
```

```
template <maybe T, class U, class R = common_type_t<iter_reference_t<T>, U&&>>>
constexpr auto value_or(T&& m, U&& u) -> R;
```

- <sup>1</sup> *Mandates:* `T` models `maybe_common_type_t<iter_reference_t<T>, U&&>::type` is defined
- <sup>2</sup> *Returns:* `bool(m) ? static_cast<R>(*m) : static_cast<R>(forward<U>(u))`.

```
template <maybe T, class U, class R = common_reference_t<iter_reference_t<T>, U&&>>
constexpr auto smd::reference_or(T&& m, U&& u) -> R;
```

- <sup>3</sup> *Mandates:* `T` models `maybe_common_reference<iter_reference_t<T>, U&&>::type` is defined
- <sup>4</sup> *Constraints:* `!reference_constructs_from_temporary_v<R, U> !reference_constructs_from_temporary_v<R, T>`
- <sup>5</sup> *Returns:* `bool(m) ? static_cast<R>(*m) : static_cast<R>((U&&)u)`

```
template <maybe T, class I,
        class R = common_type_t<iter_reference_t<T>, invoke_result_t<I>>>
constexpr auto or_invoke(T&& m, I&& invocable) -> R;
```

- <sup>6</sup> *Mandates:* `T` models `maybe_common_type<iter_reference_t<T>, invoke_result_t<I>>::type` is defined
- <sup>7</sup> *Returns:* `bool(m) ? static_cast<R>(*m) : static_cast<R>(invocable())`

Modify 22.5 Optional objects[optional]

Add to 22.5.2 Header `<optional>` synopsis

```
template <class T, class R>
constexpr auto yield_if(bool b, T&& t) -> R;
```

Add 22.5.X

### ◆.◆.3 yield\_if

[optional.yield\_if]

```
template <class T, class R = optional<decay_t<T>>>
constexpr auto yield_if(bool b, T&& t) -> R;
```

<sup>1</sup> Returns: b ? forward<T>(t) : R.

Modify 26.2 Header <ranges> synopsis

### ◆.2 Header <ranges> synopsis

[ranges.syn]

```
//◆.◆.1, nullable view
template<typename T>
requires see below;
class nullable_view; //freestanding

template<class T>
constexpr bool
enable_borrowed_range<nullable_view<T*>> = true; //freestanding

template<class T>
constexpr bool
enable_borrowed_range<nullable_view<T&>> = true; //freestanding

namespace views {
    inline constexpr unspecified nullable = unspecified; //freestanding
}
```

### ◆.◆.1 Nullable View

[range.nullable]

#### ◆.◆.1.1 Overview

[range.nullable.overview]

- <sup>1</sup> nullable\_view is a range adaptor that produces a view with cardinality 0 or 1. It adapts object types which model the exposition only concept nullable\_object\_val or nullable\_object\_ref.
- <sup>2</sup> The name views::nullable denotes a customization point object (??). Given a subexpression E, the expression views::nullable(E) is expression-equivalent to nullable\_view<decay\_t<decltype((E))>>(E).

#### ◆.◆.1.2 Class template nullable\_view

[range.nullable.view]

[Example 1:

```
optional o{4};
for (int k : nullable_view m{o})
    cout << k; //prints 4
```

— end example]

#### ◆.◆.1.3 Class template nullable\_view

[range.nullable.view]

```
namespace std::ranges {
    template<class I>
    concept readable_references = see below; //exposition only

    template<class I>
    concept nullable_object = see below; //exposition only

    template<class I>
    concept nullable_object_val = see below; //exposition only

    template<class I>
    concept nullable_object_ref = see below; //exposition only
```

```

template <typename Nullable>
    requires(copyable_object<Nullable> &&
             (nullable_object_val<Nullable> || nullable_object_ref<Nullable>))
class nullable_view<Nullable>
    : public ranges::view_interface<nullable_view<Nullable>> {
private:
    using T = remove_reference_t<
        iter_reference_t<typename unwrap_reference_t<Nullable>>>;

    movable_box<Nullable> value_; // exposition only (see ??)

public:
    constexpr nullable_view() = default;

    constexpr explicit nullable_view(Nullable const& nullable);

    constexpr explicit nullable_view(Nullable&& nullable);

    template <class... Args>
        requires constructible_from<Nullable, Args...>
    constexpr nullable_view(in_place_t, Args&&... args);

    constexpr T*      begin() noexcept;
    constexpr const T* begin() const noexcept;
    constexpr T*      end() noexcept;
    constexpr const T* end() const noexcept;

    constexpr size_t size() const noexcept;

    constexpr auto data() noexcept;

    constexpr const auto data() const noexcept;

    friend constexpr auto operator<=>(const nullable_view& l,
                                     const nullable_view& r);

    friend constexpr bool operator==(const nullable_view& l,
                                     const nullable_view& r);
};

```

<sup>1</sup> The exposition-only *readable\_references* concept is equivalent to:

```

template<class Ref, class ConstRef>
concept readable_references = // exposition only
    is_lvalue_reference_v<Ref> &&
    is_object_v<remove_reference_t<Ref>> &&
    is_lvalue_reference_v<ConstRef> &&
    is_object_v<remove_reference_t<ConstRef>> &&
    convertible_to<add_pointer_t<ConstRef>, const remove_reference_t<Ref>*>;

```

<sup>2</sup> The exposition-only *nullable\_object* concept is equivalent to:

```

template<class I>
concept nullable_object = // exposition only
    is_object_v<I> && requires(I& t, const I& ct) {
    bool(t);
    bool(ct);
    *(t);
    *(ct);
};

```

<sup>3</sup> When an object is contextually convertible to `bool` and dereferencable via operator `*`(), the object is said to be *nullable*.

<sup>4</sup> The exposition-only *nullable\_object\_val* concept is equivalent to:

```

template<class I>
concept nullable_object_val =                // exposition only
nullable_object<T>
&& readable_references<iter_reference_t<T>, iter_reference_t<const T>>;

```

5 When an object is contextually convertible to `bool` and dereferencable via operator `*`(`*`), the object is said to be a *nullable object*.

6 The exposition-only *nullable\_object\_ref* concept is equivalent to:

```

template<class I>
concept nullable_object_ref =                // exposition only
is-ref-wrapper<I>
&& nullable_object_val<typename I::type>;

```

7 `constexpr explicit nullable_view();`

8 *Effects:* Initializes *value\_* with `nullptr`

```
constexpr explicit nullable_view(Nullable nullable);
```

9 *Effects:* Initializes *value\_* with `addressof(nullable)`

```
constexpr T* begin() noexcept;
constexpr const T* begin() const noexcept;
```

10 *Returns:* `data()`;

```
constexpr T* end() noexcept;
constexpr const T* end() const noexcept;
```

11 *Returns:* `data() + size()`;

```
static constexpr size_t size() noexcept;
```

12 *Effects:* Equivalent to:

```

if (!value_)
    return 0;
Nullable& m = *value_;
return bool(m);

```

```
constexpr T* data() noexcept;
constexpr const T* data() const noexcept;
```

13 *Effects:* Equivalent to:

```

if (!value_)
    return nullptr;
const Nullable& m = *value_;
return m ? addressof(*m) : nullptr;

```

#### ◆◆.1.4 Class template specialization `nullable_view<T&>`

[range.nullable.view.ref]

```

template <typename Nullable>
requires(movable_object<Nullable> &&
(nullable_object_val<Nullable> || nullable_object_ref<Nullable>))
class nullable_view<Nullable&>
: public ranges::view_interface<nullable_view<Nullable>> {
private:
    using T = remove_reference_t<
        iter_reference_t<typename unwrap_reference_t<Nullable>>>;

    Value* value_ ; // exposition only

public:
    constexpr nullable_view() : value_(nullptr){};

    constexpr explicit nullable_view(Nullable& nullable);

    constexpr explicit nullable_view(Nullable&& nullable) = delete;

```

```

constexpr T*      begin() noexcept;
constexpr const T* begin() const noexcept;
constexpr T*      end() noexcept;
constexpr const T* end() const noexcept;

constexpr size_t size() const noexcept;

constexpr T* data() noexcept;

constexpr const T* data() const noexcept;
};

1  constexpr explicit nullable_view();
2  Effects: Initializes value_ with nullptr

constexpr explicit nullable_view(Nullable nullable);
3  Effects: Initializes value_ with addressof(nullable)

constexpr explicit nullable_view(Nullable&& nullable) = delete;
4  Deleted

constexpr T* begin() noexcept;
constexpr const T* begin() const noexcept;
5  Returns: data();

constexpr T* end() noexcept;
constexpr const T* end() const noexcept;
6  Returns: data() + size();

static constexpr size_t size() noexcept;
7  Effects: Equivalent to:
    if (!value_)
        return 0;
    return bool(*value_);

constexpr T* data() noexcept;
constexpr const T* data() const noexcept;
8  Effects: Equivalent to:
    if (!value_)
        return nullptr;
    return *value_ ? addressof(**value_) : nullptr;

```

## ◆.◆.2 Feature-test macro

[[version.syn](#)]

Add the following macro definition to [[version.syn](#)], header <version> synopsis, with the value selected by the editor to reflect the date of adoption of this paper:

```
#define __cpp_lib_ranges_nullable 20XXXXL // also in <ranges>, <tuple>, <utility>
```

## 11 Impact on the standard

A pure library extension, affecting no other parts of the library or language.

The proposed changes are relative to the current working draft [N4958].

## Document history

- R12,
- Paper system title issues - no text changes

- **Changes since R11,**
  - Expand on design and implementation details
  - Monadic functions use deducing `this`
  - Constraints, Mandates, Returns, Effects clean up
- **Changes since R10,**
  - Complete History in history section
  - `exposid` formatting and ampersand escaping TeX formatting nits
- **Changes since R9,**
  - Fix Borrowed Ranges post naming split
  - Clarify safety concerns
- **Changes since R8,**
  - Give maybe and nullable distinct template names
  - Propose T& specializations
  - Propose monadic interface for `maybe_view`
  - Wording++
  - Freestanding
- **Changes since D7,** presented to SG9 on 2022.07.11
  - Layout issues
  - References include paper source
  - Citation abbreviation form to ‘abstract’
  - ‘nuunable’ typo fix
  - Markdown backticks to `tcode`
  - ToC depth and chapter numbers for Ranges
  - No technical changes to paper – all presentation
- **Changes since R7**
  - Update all Wording.
  - Convert to standards latex macros for wording.
  - Removed discussion of list comprehension desugaring - will move to `yield_if` paper.
- **Changes since R6**
  - Extend to all object types in order to support list comprehension
  - Track working draft changes for Ranges
  - Add discussion of `_borrowed_range_`
  - Add an example where pipelines use references.
  - Add support for proxy references (explore `std::pointer_traits`, etc).
  - Make `std::views::maybe` model `std::ranges::borrowed_range` if it’s not holding the object by value.
  - Add a const propagation section discussing options, existing precedent and proposing the option that the author suggests.
- **Changes since R5**
  - Fix reversed before/after table entry
  - Update to match C++20 style [N4849] and changes in Ranges since [P0896R3]
  - `size` is now `size_t`, like other ranges are also
  - add synopsis for adding to ‘<ranges>’ header
  - Wording clean up, formatting, typesetting

- Add implementation notes and references
- **Changes since R4**
  - Use `std::unwrap_reference`
  - Remove conditional ‘noexcept’ness
  - Adopted the great concept renaming
- **Changes since R3**
  - Always Capture
  - Support `reference_wrapper`
- **Changes since R2**
  - Reflects current code as reviewed
  - Nullable concept specification
  - Remove `Readable` as part of the specification, use the useful requirements from `Readable`
  - Wording for `views::maybe` as proposed
  - Appendix A: wording for a `view_maybe` that always captures
- **Changes since R1**
  - Refer to `views::all`
  - Use wording ‘range adaptor object’
- **Changes since R0**
  - Remove customization point objects
  - Concept ‘Nullable’, for exposition
  - Capture rvalues by decay copy
  - Remove `maybe_view` as a specified type

## References

- [N4958] Thomas Köppe. N4958: Working draft, programming languages – c++. <https://wg21.link/n4958>, 8 2023.
- [P0323R9] JF Bastien and Vicente Botet. P0323R9: `std::expected`. <https://wg21.link/p0323r9>, 8 2019.
- [viewmayb27:online] Steve Downey. A view of 0 or 1 elements: `views::maybe`. [https://github.com/steve-downey/view\\_maybe/blob/master/papers/view-maybe.tex](https://github.com/steve-downey/view_maybe/blob/master/papers/view-maybe.tex), 07 2022. (Accessed on 08/15/2022).